



Pivan

Profile- double cylinder CLIQ[®] Go N531,SERVICE=CLIQGo

Without key

Product description

- Available as rotary secured or electronical version (V=)
- Other side can feature an electronic or rotary-secured design
- Brass cylinder housing components
- Standard finish, satin nickel-plated (OF=MV)
- Basic cylinder length 61 mm (C) A/B (L=30/30) other installation lengths available flexible modular system
- Optional, differing basic cylinder length of 56 mm (C) A/B (L=28/28)
- Standard locking cam position (SST=30°); differing locking bit position available, optionally available with SST=FLEX
- Optionally available with double locking cam (VAR=K901310-X-BIFFAR)
- Optional with SST=FZG possible
- Optionally available with anti drilling protection class 2 (AB=2)
- Both side locking (GE=BS) and 360° free-wheeling function as standard
- Cam made of break-proof, corrosion-resistant stainless steel
- Maintenance-free for up to 200,000 cycles
- Splash-proof IP54
- Dust and rain protection cap available for one or both sides (SUR=3/-, -/3, 3/3) IP55

Scope of delivery

- 1 profile-double cylinder
- 1 cylinder fixing screw M5 x 85 mm

Suitable ASSA ABLOY products

- Steel security fitting with cylinder cover handle/handle S403
- Steel security fitting with cylinder cover round knob/handle S406
- Steel security fitting with cylinder cover angled knob/handle S408
- Steel security fitting with cylinder cover handle/handle S413
- Steel security fitting with cylinder cover angled knob/handle S418
- Steel security fitting with cylinder cover round knob/handle S416
- Steel security fitting with cylinder cover handle/handle S423
- Steel security fitting with cylinder cover round knob/handle S426
- Steel security fitting with cylinder cover angled knob/handle S428

Variants that can be ordered

Article number	OF=	L=	V=
N531,SERVICE=CLI QGo	MV/MV	30/30	D/D
	MV/MV	30/30	E/D
	MV/MV	30/30	D/E
	MV/MV	30/30	E/E



