Premium lock, gear mechanism

Sliding bolt + two hooks

2230G series

Gear Mechanism

- · It allows a smooth operation of the lock.
- · It reduces the risks of failure of the lock.

Three independent locking points.

- · It is necessary to break the three points one by one to force the lock.
- \cdot 2 hook + sliding bolt.

The cases, with 15mm of wide, reduce the aluminium mechanization.

- » Flat profile face plate, length of 2030mm.
- » Face plate and strike plates made in stainless steel.
- » Adjustable latch.

Options					
Cylinder cam	15 mm				
Latch	Adjustable				
Front plate	Flat				
Accesories					
Escutcheons	E190	E205	E240		
Strikes	C22	Adjustable	Electric		

CYL	STR	ESC
•	Α	•
•	Α	•
•	Α	•
	Α	•
	Α	•
	Α	•

2231G	Cylinder	Backsets	Product code	CYL	STR	ESC
		25	2231G2555RSI	•	Α	•
	TE-5	30	2231G3055RSI	•	Α	•
		35	2231G3555RSI	•	Α	•
	Cylinder	25	4231G255SRSI		Α	•
	not	30	4231G305SRSI		Α	•
	included	35	4231G355SRSI		Α	•

2236G	Cylinder	Backsets	Product code	CYL	STR	ESC
		25	2236G2555RSI	•	Α	•
	TE-5	30	2236G3055RSI	•	Α	•
		35	2236G3555RSI	•	Α	•
	Cylinder	25	4236G255SRSI		Α	•
	not	30	4236G305SRSI		Α	•
	included	35	4236G355SRSI		Α	•

CYL: cylinder TE5 50303040N // ESC: 2 units 44200NE escutcheons STR: stainless steel strikes. A = 1 unit. C2210XNOX + 2 units C2230XNOX //

