

Vingcard E100

Electronic Lock

The Vingcard E100 with RFID reader is compatible with your Vingcard Visionline system.

With a wide range of escutcheons for different regions and cylinder profiles, the E100 can be used with a variety of standard and narrow profile lock cases. The range is suitable for both guest room doors and back of house applications where the door types can vary.



FEATURES

- : Supports narrow style doors (down to 40mm backset).
- : Rugged stainless steel finish.
- : Suitable for mixed Vingcard installation.
- : Cylinder cut-outs for DIN, Scandinavian and Swiss versions.
- : Quick and easy installation.
- : Fully compatible with Visionline and Lock Service.
- : Minimalistic and modern design.
- : IP rating (IP52) - (not for outdoor use).
- : Battery capacity for 40,000 openings.

vingcard
ASSA ABLOY

Experience a safer
and more open world

TECHNICAL DATA

Approvals:	Standard: CE Premium version: EN179, EN1906, DIN18273
Dimensions:	312 x 41 x 10/20 mm (H x W x D)
Handle Versions	Standard escutcheons: L-Shape, U-Shape Premium escutcheons: U-Shape
Escutcheon Finish:	Stainless steel brushed (ST)
Door Thickness:	DIN: Door leaf between 40 and 100 mm thick, in 10 mm increments. Scandinavian and Swiss: Door leaf between 35 and 95 mm thick, in 10mm increments.
Mounting Plate:	Scandinavian: 45 mm or 55 mm
Backset:	> 40 mm
Battery:	1 x Lithium CR123A
Battery Life:	> 40,000 cycles (for max. 3 years)
Class of Protection:	IP 52 (not for outdoor use)
Operating Temperature Range:	Standard: 0°C to 60°C Premium: -25°C to 60°C
Humidity:	< 85% (condensation-free)
Status:	LED (red/green/orange)
RFID Technology:	Mifare Classic, Mifare UL EV1
Mobile Access Support:	No
Online Support:	No
Interface:	Micro USB firmware download and battery back up

