



Product description

Version with magnet bolt counterpart, with fail-unlocked strike 138TQ53

Overview of Advantages

- Latch insertion on the door frame removed
- Visually attractive, concealed installation, magnet bolt is retracted when door open
- Low opening force due to weak latch bolt spring
- No closing force due to magnet bolt
- Quiet locking and unlocking
- The supplementary locking system 9338 is designed as a supplementary locking system for versatile applications for the locking of doors
- Example for other usage options: Office doors, laboratory doors, interlocks, wet cells in hospitals, special doors
- Universal installation position, vertical and horizontal
- Compatible with model 9334
- Load cycles for factory test: 1,000,000

Scope of delivery

- Delivery with magnet bolt counterpart and fail-unlocked strike 138TQ53 and stainless steel strike plate no. 34G

Technical data

DIN-direction	Universal
potential	12 V DC
Adjustable keeper (FF, FaFix®)	Yes
Noise reduction	Yes
Diode (05)	Yes
Fail-unlocked	Yes
Weak latch bolt spring	Yes
Input operating voltage	± 10%
Current consumption 12 V DC	235 mA
Max. start current consumption at 12 V DC	280 mA
Max. pre-load	30 N
Bolt throw	10 mm
material bolt	Plastic
Installation position	Vertical and horizontal
Operating temperature range	-15 °C to +40 °C
Break-in resistance	3000 N
Latch bolt engaging depth	5,5 mm
FaFix® adjustment range	4 mm
Load cycles for in-plant test	1000000

Accessories/Individual parts

Order number	Product
-----68835-01	Flat striking plate no. 688
-----68935-01	Flat striking plate no. 689

Article number	9338---34G35E91
----------------	-----------------