

Product description

The MEDIATOR® lock in its tubular frame version is available with different backsets and a comprehensive range of accessories.

Overview of Advantages

- Automatic locking system: Bolt and latch are blocked, therefore higher level of security
- Mechanical follow up control between double action latch and control latch
- Integrated panic function via internal door handle
- Changeover function for unlocking with a key from the outside
- Minimum rear backset for tubular frame design: 15 mm

Scope of delivery

- 1 lock
- 1 reducer

Note

- MEDIATOR® locks have a bolt through the handle and thus require front door furniture (inside handle or panic push bar, outside knob or push bar).

Technical data

Backset	30 mm
Distance	92 mm
Type of cylinder	Euro profile cylinder
Bolt throw	20 mm
Handle follower	9 mm
VdS-approval	G 109 032, M 109314, Z 109001
Approval DIN EN 179	Certificate of Constancy of performance 0432-CPR-00007-11
DIN EN 1125 approval	Certificate of Constancy of performance 0432-CPR-00007-12
Building authorities test certificate	P-120003555
Mech. strength (EN 12209:2004)	200,000 cycles, 50N load on latch, Class 6 protection
Width face plate	24 mm
Face plate shape	square, flat
DIN-direction	Universal

Accessories/Individual parts

Order number	Product
Z09-DBRR3-----00	Distance plate 300 x 24 x 3 mm
65.000010	Sliding part 100 x 30 x 3 mm

Article number	609-102PZ-----1
EAN	4042203344679

