



VALKYRIE CS IP65

CONVENTIONAL WALL MOUNT
SOUNDER/ BEACON
OUTDOOR USE-IP65



1328-CPR-0300
CERTIFIED

The VALKYRIE CS IP65 is a wall mounted Conventional Sounder/ Beacon with low power consumption. It is specifically designed to be used outdoors. Four different tones are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections allowing for the presence of differentiated evacuation and alert sounds.

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	20 V to 30 V DC
CURRENT - SOUNDER/BEACON ACTIVE	10 mA - 280 mW @ 28 V DC
MAXIMUM SOUNDER OUTPUT	95,3 dB (@ 1 meter - 30 V DC)
RESET/START-UP TIMES	20 seconds max.
PROTECTION CATEGORY	Type B - Outdoor Use / Bucins: M20x1.5 IP65 4-9mm (recommended)
CABLE SIZE	0.5-2.5 mm ²
COLOUR	Red
CASE MATERIAL	ABS and PC - Flame Retardant rating UL 94 V2
OPER. TEMPERATURE	-25°C to 70°C
MAX. HUMIDITY	95% RH Non-Condensing
DIMENSIONS	112 (D) x 110 (H) mm inc. base
WEIGHT	315 g inc. base & 350 g inc. packaging

For EN54-13 compliance, please check the control panel manual specifications.

ORDER CODE

VALKYRIE CS IP65	CONVENTIONAL WALL SOUNDER - IP65 RATED	1328-CPR-0300
VALKYRIE CSB IP65	CONVENTIONAL WALL SOUNDER/ BEACON - IP65 RATED	1328-CPR-0300