

# Electric strike for outdoor areas

## 118WE-----A71



### Product description

Model with mechanical unlocking.

### Overview of Advantages

- Water-proof for use outdoors
- Protection rating IP54 for the electrical components
- Connecting cable 300 mm length
- Equipped with bipolar protective diodes
- Radius keep, FaFix®, adjustable by 3 mm
- Compatible with current mortise locks
- Striking plates with 2 position settings available
- Symmetrical design. DIN left/right as well as horizontal applicable

### Scope of delivery

- 1 piece electric strike

### Technical data

DIN direction	Universal
potential	10-24 V AC/DC
Adjustable keeper (FF, FaFix®)	Yes
Mechanical unlocking (E)	Yes
Fail-locked	Yes
Bi-directional diode	Yes
Continuous duty	11-13 V DC
Current consumption 12 V AC	250 mA
Current consumption 12 V DC	280 mA
Current consumption 24 V AC	500 mA
Current consumption 24 V DC	560 mA
Break-in resistance	3750 N
Height	66 mm
Width	17,5 mm
Depth	26 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-40 °C to +50 °C
Installation position	Vertical and horizontal
Load cycles for in-plant test	250000
Max. latch preload AC	200 N
Max. latch preload DC (stabilised)	50 N

Article number 118WE-----A71

