

Fire protection fitting for narrow style doors

J-shaped handle with outside handle

Product description

- The fire protection fitting for narrow style doors meets requirements for fire and smoke protection hardware in accordance with DIN 18273. The high-quality J-shaped handle on oval rose blends elegantly into any building. Durable brushed stainless steel as a modern and corrosion-resistant material is perfect for any environment where quality matters. This model is supplied with an outside handle.

Overview of Advantages

- Freely configurable to your door thickness
- Classic curved handle
- Meets requirements for fire and smoke protection Hardware in accordance with DIN 18273

Note

- Compatible with locks of series N1556

Technical data

Exterior escutcheon	Handle
Protection rating	0
Handle	J-shaped
Type of cylinder	Profile cylinder
Handle spindle	9 mm
Material	Standard, brushed stainless steel
Mounting	Long plate
Distance	92 mm
DIN-direction	DIN left/right with spring assist

Accessories/Individual parts

Order number	Product
HA32S0000196000	Mounting set protection fitting, narrow style, protection rating 2 with panic spindle for door leaf thickness 35-39 mm with panic spindle for door leaf thickness 35-39 mm
HA32S0000197000	Mounting set protection fitting, narrow style, protection rating 2 with panic spindle for door leaf thickness 40-44 mm with panic spindle for door leaf thickness 40-44 mm
HA32S0000198000	Mounting set protection fitting, narrow style, protection rating 2 with panic spindle for door leaf thickness 45-49 mm with panic spindle for door leaf thickness 45-49 mm
HA32S0000199000	Mounting set protection fitting narrow style protection rating 2 with panic spindle for door leaf thickness 50-54 mm with panic spindle for door leaf thickness 50-54 mm
HA32S0000200000	Mounting set protection fitting, narrow style, protection rating 2 with panic spindle for door leaf thickness 55-59 mm with panic spindle for door leaf thickness 55-59 mm
HA32S0000201000	Mounting set protection fitting, narrow style, protection rating 2 with panic spindle for door leaf thickness 60-64 mm with panic spindle for door leaf thickness 60-64 mm
HA32S0000202000	Mounting set protection fitting, narrow style, protection rating 2 with panic spindle for door leaf thickness 65-69 mm with panic spindle for door leaf thickness 65-69 mm
HA32S0000203000	Mounting set protection fitting, narrow style, protection rating 2 with panic spindle for door leaf thickness 70-74 mm with panic spindle for door leaf thickness 70-74 mm
HA32S0000204000	Mounting set protection fitting, narrow style, protection rating 2 with panic spindle for door leaf thickness 75-79 mm with panic spindle for door leaf thickness 75-79 mm
HA32S0000205000	Mounting set protection fitting, narrow style, protection rating 2 with panic spindle for door leaf thickness 80-84 mm with panic spindle for door leaf thickness 80-84 mm

Article number	H43200150900000
----------------	-----------------

