

Cylinder for profile doors



Lock is operated by key from outside and by thumbturn inside the door.

- Overview of Advantages

 Can be use with wide range of Scandinavian and Finnish type mortice lock cases for narrow stile doors Strong burglary protection

- Suitable for both outer and inner door use
 Adjustable during installation to match different door thicknesses
 Several plating options, also antimicrobial paints



Technical data

Available key systems	ABLOY PROTEC, ABLOY PROTEC ² , ABLOY NOVEL
Available plating options	Bright chrome (Cr), Satin chrome (HCr), Brushed nickel (NiHa), Antimicrobial painted ACTIVE Val (white)/ Mus (black)/Har (gray)/Gra (graphite)
Cylinder shield dimensions	85 x 34mm, height 27mm
Thumbturn plate dimensions	85 x 32mm
Weight	0,58kg
Possible door thicknesses:	42111mm

This content is protected by Intellectual Property Rights Laws. The title to the content shall not pass to you, and instead shall remain with Abloy Oy or a third party holding the title. Abloy develops continuously the products and solutions offered. Therefore, the information contained in the document is subject to change without notice. ABLOY PROVIDES THIS CONTENT ON AN "AS IS" BASIS WITHOUT ANY WARRANTIES OF ANY KIND, EXPRESS, IMPLIED, OR STATUTORY."

