



Installation Devices / Guard Units

Product Code

F09423

DUOX PLUS AUDIO VEO GUARD UNIT

Reference EAN

9423 8424299094236

Description.

Description

FUNCTIONS

- 4 mechanical buttons with pleasant touch for basic functions
- Headset with magnet for easy hanging.
- Audio Full-Duplex.
- Privacy in conversation.
- Red status LED.
- Capacitive and panoramic touch screen (size 4.3" and format 16:9). Resolution 480 x 272 pixels.
- Make calls to homes, outdoor panels or concierge.
- The concierge can transfer the call to a flat or to another concierge.
- Reception of calls from dwellings, outdoor panels or other guard units.
- Communication between two dwellings through the caretaker.
- Establishing a connection with the outdoor panels to open the door. List of selectable outdoor panels of the installation. User interface in 28 languages. 10 selectable ring tones.

Call duration 30 s.

- 8 volume levels. Volume level can be selected for calls, conversation and touch screen sound.
- No-message mode (ring tone mute). -

Fermax / Products 1/3 thanks to **♦ sales layer**



Deactivation of the microphone during the conversation (Mute).

- Registration of missed calls. Maximum of 50 calls of each type (houses, outdoor panels, guard units).
- Screen brightness control (8 levels).
- Selection between 3 operation modes: Day, Mixed and Night. Day: receives calls from access points and homes. The calls from the panel to the home are always sent to the guard unit. Mixed: calls from the panel are received in the home and can also be configured to be diverted to the guard unit after 15 seconds. Night: only allows calls to homes. No call is received.
- Some configuration menus have restricted access by pin code. Different code for installer and janitor.
- Possibility of programming terminals (monitors and telephones) from the central guard unit.
- Winter/Summer time configuration with 3 options: Europe, America or manual. Available in 12h or 24h format. 3 different date formats: DD/MM/YYYY, MM/DD/YYYY, YYYY/MM/DD.
- Agenda for up to 10,000 home users, 70 outdoor panels and 30 concierge panels. It is possible to search by name.
- Touch screen lock function for cleaning.
- Possibility of connecting a call extension (ref. 2040) or a light and bell activator (ref. 2438) through terminals "-" and "A".
- Tabletop support included, made of high quality stainless steel (AISI316L) and resistant to corrosion.

 BASIC PUSHBUTTON OPERATORS MENU: access to the main menu on the screen, easy to use for the operation and configuration of parameters. Door opening. To make calls to homes, panels and caretakers. See missed calls register. LEDs Red LED off when the screen is activated. Red LED on when the screen is off. Red LED flashes when there are missed calls pending to be

Technical Details

checked.

MECHANICAL FEATURES

Color: Black Material: ABS with UV protection. DIMENSIONS 200 x 200 x 46 mm. Desktop support (316L quality stainless steel support). Stand inclination: 60°

TECHNICAL FEATURES

PSU: - 18-24 Vdc Estimated maximum consumption: - Standby (display off): 75 mA. - Conversation with audio at maximum: 255 mA. - Call with volume at maximum: 270 mA. Operating temperature: 5°C, +40°C] / [41°F, 104°F]. Operating humidity: 0%, 90%] Capacitive touch screen: - Size 4.3"; Format 16:9 - Resolution: 480 x 272 Audio features: - Digital DUOX PLUS audio. - Speakers: 1 x 1W. Technology: digital DUOX PLUS system (2 non-polarized wires) No. of guard units per installation: 10 in General Entrance / 10 per Block

TECHNICAL SPECIFICATIONS

CONNECTIONS B, B: DUOX PLUS bus. +A: connection for external devices (call extension ref. 2040, light and bell activator ref. 2438). -: negative (electrical reference). +12V: 12Vdc output (not used in this product). P: connection not used in this product. A, B: RS485 bus (not used in this product). Terminal block with RJ45 connector to facilitate connection/disconnection with the DUOX PLUS bus.

Fermax / Products 2/3 thanks to **♦ sales layer**



Details.

Weight (kg)

2.1048

Packaging measurements

(height x width x depth) cm

26,5x21x17

Video Door Entry system

Technologie

DUOX


Manuals

970034Elb_Central_Conserjeria_Veo_Duox_Plus_V07_20.pdf 970034FAPb Central Conserjeria Veo Duox Plus V07_20.pdf


Declaration of conformity


DOCF09423EN.pdf

Other images



Back view





Fermax / Products 3/3