



VALKYRIE AS

ADDRESSABLE WALL MOUNT SOUNDER/ BEACON



The VALKYRIE AS is a Wall Mounted Addressable Sounder/ Beacon with low power consumption. Up to 32 individually addressed sounders can be installed per loop occupying address 94 to 125. The address is set using switches 1 to 5 of the 8 way DIL switch. Four different tones are available and selected using DIL switches 6 and 7.

When individual address reporting is not required, VALKYRIE AS can be configured as a Shadow Sounder. In this case sounders do not occupy an address in the loop thus freeing up addresses for more detection devices. Shadow sounders do not report back to the control panel so their presence on the loop is not monitored. Shadow sounders draw current from the loop (10 mA in alarm) and must be included in loop load calculations.

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	Loop Powered - 20 V to 30 V DC
LOOP CURRENT - QUIESCENT	550 uA max. with isolator
LOOP CURRENT - SOUNDER/BEACON ACTIVE	10 mA - 280 mW @ 28 V DC inc. isolator
MAXIMUM SOUNDER OUTPUT	100 dB (@ 1 meter - 30 V DC)
CABLE SIZE	0.5-2.5 mm ²
RESET/START-UP TIMES	20 seconds max.
PROTECTION CATEGORY	Type A - Indoor Use / Rating IP21C
COLOUR / CASE MATERIAL	White or Red / ABS and PC
OPER. TEMPERATURE / MAX. HUMIDITY	-10°C to 55°C / 95% RH Non-Condensing
DIMENSIONS	110 (D) x 85 (H) mm inc. base
WEIGHT	254 g inc. base & 304 g inc. packaging

For EN54-13 compliance, please check the control panel manual specifications.

ORDER CODE

VALKYRIE AS	ADDRESSABLE WALL SOUNDER	1328-CPR-0286
VALKYRIE ASB	ADDRESSABLE WALL SOUNDER/ BEACON	1328-CPR-0286
VALKYRIE ASI	ADDRESSABLE WALL SOUNDER WITH ISOLATOR	1328-CPR-0286
VALKYRIE ASBI	ADDRESSABLE WALL SOUNDER/ BEACON WITH ISOLATOR	1328-CPR-0286

