

## 1/W MILO VIDEO PANEL MEET



**Reference:** 9533

**1/W VIDEO MEET PANEL** is presented in two different versions: one version with IC reader, the other one without reader.

### FEATURES

- Aluminum Profile
- High Resistance Tempered Glass
- High Definition...

---

## DESCRIPTION

**1/W VIDEO MEET PANEL** is presented in two different versions: one version with IC reader, the other one without reader.

### FEATURES

- Aluminum Profile
- High Resistance Tempered Glass
- High Definition Colour Camera
- Low Power Consumption
- Wide Range Working Environment
- Linux Modular Structure
- Access Control Integrated (Only for Panel with Reader)
- Available In 10 Languages
- Remote Firmware Update

### FUNCTIONS

#### CALL TENANT

Visitors are able to call the desired tenant from 1L panel. Alternatively, it can be configured to call one guard unit acting as an emergency call panel.

### REFERENCES

- Ref. 9533 1/W VIDEO MEET PANEL
- Ref. 9534 1/W VIDEO MEET PANEL (+ PROXIMITY)
- Ref. 9543 MEET PANEL FLUSH BOX – S



## TECHNICAL SPECIFICATIONS

### System:

- CPU: ARM Cortex-A7 1.2GHz
- FLASH: 128M
- SDRAM: 64M

### Audio Features:

- G.711 protocol
- Audio level 17.7 dB

### Camera:

- 1/3" CMOS Color
- 90o visual angle: Vertical 72°, Horizontal 54°
- 1.3 Mega Pixels
- Minimum illumination 0.5 LUX
- AWB

### LED:

- White LED
- LM 60 mA Min. 24, Typ. 26
- View Angle 2θ1/2: 120

### Power Consumption:

- On standby: 125mA
- Working: 250mA

### Working voltage:

- 12 VDC

### Connectivity:

- Ethernet RJ-45 Connector
- Exit button and door sensor connection
- NO, C, NC: Door lock release connection
- Built in web server for configuration and remote management

### Working Environment:

- Temperature: -10 oC – 70 oC
- Humidity: 20 – 80% (Non-condensing)
- IP 54

**Weight:** 1,0445 kg

**Size of product when packed:** 8x25,5x16,5 cm

**EAN 13:** 8424299095332