




# ZEOS-AS

## INTELLIGENT ADDRESSABLE FIRE DETECTORS WITH SMART ADDRESSING



The ZEOS-AS series of Intelligent Addressable Detectors have been designed to be fully compatible with GFE's addressable fire alarm control panels, JUNIOR, JUNO NET, GEKKO, OCTO+ and G-One.

The ZEOS detector range, in conjunction with GFE's panels, contains algorithms that can accommodate several Alarm thresholds and timed options in combined smoke and heat detectors variants.

The ZEOS-AS series is certified to EN54-5 and EN54-7 and consists of combined photoelectric smoke and heat detectors. Optionally they can be fitted with a short-circuit loop isolator. The ZEOS-AS range of fire detectors is not addressed using a D.I.L. switch, it uses instead GFE's proprietary Smart Addressing Mechanism (SAM). The address can be set either by using GFE's intelligent device programmer or alternatively, when used in conjunction with GFE's range of Intelligent Addressable Fire Detection Panels, GFE's automatic address setting mode ASET.

### KEY FEATURES

- Dual LEDs for 360° visibility
- Advanced detection and communication protocols
- Easy installation and maintenance
- Sleek low-profile housing
- Durable sensor head, no need for replacement
- SMD circuit board design
- High quality and reliability guaranteed.

### TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	Loop Powered - 17V to 30V DC
CURRENT - QUIESCENT / SURGE	450 uA max.
CURRENT - DEVICE IN ALARM	4 mA - Alarm LED illuminated
SENSITIVITY	According to EN54-5 or/and EN54-7, EN54-17
CABLE SIZE	0.5-2.5 mm <sup>2</sup>
RESET/START-UP TIMES	20 seconds max.
COLOUR / CASE MATERIAL	White / ABS
MAX. HUMIDITY	95% RH Non-Condensing
NORMAL / TRANSIENT OPER. TEMPERATURE	0°C to 50°C / -10°C to 85°C
DIMENSIONS / WEIGHT	100 (D) x 50 (H) mm included base / 92g and 144g included base

*For EN54-13 compliance, please check the control panel manual specifications.*



**ORDER CODE**

<b>ZEOS-AS-S</b>	ANALOGUE ADDRESSABLE PHOTOELECTRIC SMOKE DETECTOR WITH SMART ADDRESSING	1328-CPR-0526
<b>ZEOS-AS-H</b>	ANALOGUE ADDR. TEMPERATURE/HEAT DETECTOR WITH SMART ADDRESSING	1328-CPR-0527
<b>ZEOS-AS-SH</b>	ANALOGUE ADDR. COMBINED SMOKE & HEAT DETECTOR WITH SMART ADDRESSING	1328-CPR-0525
<b>ZEOS-AS-SI</b>	ANALOGUE ADDR. PHOTOELECTRIC SMOKE DETECTOR W/ ISOLATOR & SMART ADDRESSING	1328-CPR-0609
<b>ZEOS-AS-HI</b>	ANALOGUE ADDR. TEMPERATURE/HEAT DETECTOR W/ ISOLATOR & SMART ADDRESSING	1328-CPR-0608
<b>ZEOS-AS-SHI</b>	ANALOGUE ADDR. COMBINED SMOKE & HEAT DETECTOR W/ ISOLATOR & SMART ADDRESSING	1328-CPR-0524

